



ULTRA SLIM FLAT ADJUSTABLE

IP 67 WATERPROOF SPOTLIGHT
INSTALLATION HEIGHT 23 MM.
3 OPTIONS: REFLECTOR/LENS/DIFFUSER



B0101-01/B1(Adjustable Spotlight)



B0101-01/C1(Adjustable Spotlight)







Power: 5W/7W
Luminous Efficiency: 85 LM/W
CRI.: 90
Beam angle: 24°/38°/60°/90°/120°
Voltage: 220V/110V
IP Rating: 21/54/65/67
Material: Aluminum

- 5year and 10year warranty
- IP21/ IP54 / IP65/ IP67
IP54 suitable for bathroom
IP65 suitable for Patio,Porch,Eave,Shower room
IP67 can be briefly immersed in water
- Flicker-free & trailing edge driver
- Adjustable and non-adjustable options
- Cut-out options: 55/68/75/83/90/115/165mm
- Small dimension, but high power and brightness.
- Light efficiency is 120lm/W Max.
- It is also possible to apply a DALI, 1-10V, 9~36V DC or ZIGBEE driver to these spots..



Triac Dimmable





DRIVER DATA SHEET(Flicker-free Driver)


Wattage	5W/7W		
Input rated Voltage	AC200-240V		AC100-265V
Frequency	50/60Hz		50/60Hz
Input Voltage	AC180-265V		AC90-305V
Efficiency	≥76%		≥83%
Power Factor	≥0.9		≥0.5
Rated input current	≤0.03A		≤0.03A
Full load output Voltage	DC8-11V	DC14-25V	DC28-42V
Rated output current	350mA	260mA	130mA
Output current range	340mA±5%	130mA±5%	130mA±5%
Power tolerance	10%		10%
Dimming range	10%-100%		PASS
Total harmonic distortion (THD)	≤20%		PASS
Current output tolerance	±5%		
Short circuit protection	PASS		
Over voltage protection	PASS		
Over temperature protection	PASS		

FIXTURE COMPATIBILITY

Rated Wattage	Electrical Classification	Ingress Protection	Operating Temp	Operating Humidity	Storage Temp
5W/7W	II	IP21/54/65	-20℃~45℃	0~90%	-20℃~65℃

PACKAGING INFORMATION

	SIZE(CM)	N.W/pc (KGS)	G.W.(KGS)	Q'TY(PCS)		CTNS	Q'TY(PCS)	VOLUME(CBM)
Carton	52.5*21.5*37	0.25	13	50	20" standard container	683	34150	28
					40" standard container	1366	68300	56






DIM TO WARM+CCT SOLUTION+2 POWER

Professional dimming LED light manufacturet

- 1** DIM TO WARM
- 1800K~2800K
 - 1800K~4000K
 - 2700K~4000K



- 2-1** 2 CCT + DIM TO WARM + 2 POWER
2000K+ 3000K+ DTW (2000K~2800K)

- 2-2** 2 CCT + DIM TO WARM + 2 POWER
2000K+ 4000K+ DTW (2000K~4000K)

- 2-3** 2 CCT + DIM TO WARM + 2 POWER
2700K+ 3000K+ DTW (2000K~2800K)

- 2-4** 2 CCT + DIM TO WARM + 2 POWER
2700K+ 4000K+ DTW (2700K~4000K)

- 2-5** 2 CCT + DIM TO WARM + 2 POWER
3000K+ 6000K+ DTW (3000K~6000K)

- 3-1** 3 CCT + DIM TO WARM + 2 POWER
2000K+2700K+3000K+ DTW (2000K~ 3000K)

- 3-2** 3 CCT + DIM TO WARM + 2 POWER
2000K+3000K+4000K+ DTW (2000K~ 4000K)

- 3-3** 3 CCT + DIM TO WARM + 2 POWER
2700K+ 3000K+ 4000K+ DTW (2000K~ 3000K)

- 3-4** 3 CCT + DIM TO WARM + 2 POWER
2700K+ 3000K+ 4000K+ DTW (2700K~ 4000K)

- 3-5** 3 CCT + DIM TO WARM + 2 POWER
3000K+4000K+6000K+ DTW (3000K~ 6000K)

- Dim to warm LED simulates the color tones of halogens
- It likes sunset to sunrise,gives you a circadian lighting.

4 **2 IN 1**
2 POWER + 3CCT SWITCH

- Power and CCT Switchable
- Multiple power box options
- 5 years and 10 years warranty options

Power :3~42W
PF:≥0.9




Flicker free and noise-free

Smooth triac Dimmable

Dimmable Range:10~100%

Dimmable power supply

CCT: 2700K/3000K/4000K
CCT: 2700K/4000K/6000K
CCT: 2500K/2700K/3000K
CCT: 3000K/4000K/5500K



5 **DRIVER INTEGRATED LED SPOTLIGHT**
Trailing edge Dimmable driver

- Driver integrated, connect to 230V directly
- Installation height as slim as 23mm
- IP54/ IP65 rating, suitable for bathroom
- 5-year warranty
- Bleow items have driver internal option:
- Deep dimming, Flicker-free & trailing edge driver

