




★ Tell the story of lighting with quality

INTEGRATED DESIGN ISOLATE CEILING UP AND DOWN,
WATERPROOF AND KEEP HEAT FROM LOOSING.



Product Display




360° TILTABLE SPOTLIGHT
Can be used under insulation directly




B0103-02/A1


Power	CCT	Lumen	CRI	IP Rating	Beam Angle
5W	2700/3000/4000K	450lm	90	65	38°/90°
5W	1800-2800K	300lm	95	65	38°/90°
7W	2700/3000/4000K	600lm	90	65	38°/90°
7W	1800-2800K	380lm	95	65	38°/90°



B0103-02/A3

Power	CCT	Lumen	CRI	IP Rating	Beam Angle
2*5W	2700/3000/4000K	900lm	90	65/67	38°/90°
2*5W	1800-2800K	600lm	95	65/67	38°/90°
2*7W	2700/3000/4000K	1200lm	90	65/67	38°/90°
2*7W	1800-2800K	760lm	95	65/67	38°/90°





DRIVER DATA SHEET(Flicker-free Driver)


Wattage	5W/7W		10W/12W
Input rated Voltage	AC100-265V		AC100-265V
Frequency	50/60Hz		50/60Hz
Input Voltage	AC90-305V		AC90-305V
Efficiency	≥83%		≥85%
Power Factor	≥0.5		≥0.5
Rated input current	≤0.03A		≤0.05A
Full load output Voltage	DC8-11V	DC14-25V	DC28-42V
Rated output current	350mA	260mA	260mA
Output current range	340mA±5%	250mA±5%	250mA±5%
Dimming range	10%-100%		****
Total harmonic distortion (THD)			≤20%
Current output tolerance			±5%
Power tolerance			±10%
Short circuit protection			PASS
Over voltage protection			PASS
Over temperature protection			PASS

FIXTURE COMPATIBILITY


Rated Wattage	Electrical Classification	Ingress Protection	Operating Temp	Operating Humidity	Storage Temp
5W/7W	II	IP21/54/65	-20℃~45℃	0~90%	-20℃~65℃

PACKAGING INFORMATION

	SIZE(CM)	N.W/PC (KGS)	G.W. (KGS)	Q'TY (PCS)
Carton	52.5*21.5*37	0.25	13	50



- 5year and 10year warranty
- IP21/ IP54 / IP65/ IP67
 - IP54 suitable for bathroom
 - IP65 suitable for Patio,Porch,Eave,Shower room
 - IP67 can be briefly immersed in water
- Flicker-free & trailing edge driver
- Adjustable and non-adjustable options
- Cut-out options: 55/68/75/83/90/115/165mm
- Small dimension,but high power and brightness.
- Light efficiency is 120lm/W Max.
- It is also possible to apply a DALI, 1-10V,9~36V DC or ZIGBEE driver to these spots..






DIM TO WARM+CCT SOLUTION+2 POWER

Professional dimming LED light manufacturet

1

DIM TO WARM

- 1800K~2800K
- 1800K~4000K
- 2700K~4000K



2-1

2 CCT + DIM TO WARM + 2 POWER
2000K+ 3000K+ DTW (2000K~2800K)

2-2

2 CCT + DIM TO WARM + 2 POWER
2000K+ 4000K+ DTW (2000K~4000K)

2-3

2 CCT + DIM TO WARM + 2 POWER
2700K+ 3000K+ DTW (2000K~2800K)

2-4

2 CCT + DIM TO WARM + 2 POWER
2700K+ 4000K+ DTW (2700K~4000K)

2-5

2 CCT + DIM TO WARM + 2 POWER
3000K+ 6000K+ DTW (3000K~6000K)

3-1

3 CCT + DIM TO WARM + 2 POWER
2000K+2700K+3000K+ DTW (2000K~ 3000K)

3-2

3 CCT + DIM TO WARM + 2 POWER
2000K+3000K+4000K+ DTW (2000K~ 4000K)

3-3

3 CCT + DIM TO WARM + 2 POWER
2700K+ 3000K+ 4000K+ DTW (2000K~ 3000K)

3-4

3 CCT + DIM TO WARM + 2 POWER
2700K+ 3000K+ 4000K+ DTW (2700K~ 4000K)

3-5

3 CCT + DIM TO WARM + 2 POWER
3000K+4000K+6000K+ DTW (3000K~ 6000K)

- Dim to warm LED simulates the color tones of halogens
- It likes sunset to sunrise,gives you a circadian lighting.

4

2 IN 1

2 POWER + 3CCT SWITCH

- Power and CCT Switchable
- Multiple power box options
- 5 years and 10 years warranty options

Power :3~42W

PF:≥0.9

Flicker free and noise-free

Smooth triac Dimmable

Dimmable Range:10~100%



Dimmable power supply

CCT: 2700K/3000K/4000K

CCT: 2700K/4000K/6000K

CCT: 2500K/2700K/3000K

CCT: 3000K/4000K/5500K



5

DRIVER INTEGRATED LED SPOTLIGHT

Trailing edge Dimmable driver

- Driver integrated, connect to 230V directly
- Installation height as slim as 23mm
- IP54/ IP65 rating, suitable for bathroom
- 5-year warranty
- Bleow items have driver internal option:
- Deep dimming, Flicker-free & trailing edge driver

