



B0112-02/A1



Power	CCT	Lumen	CRI	IP	Beam Angle	Dimension	Cut-out
7W	2700/3000/4000K	600lm	90	21	15°/24°/38°/60°	L110*W110*H85mm	L80*W80mm
7W	1800-2800K	380lm	95	21	15°/24°/38°/60°	L110*W110*H85mm	L80*W80mm
12W	2700/3000/4000K	1000lm	90	21	15°/24°/38°/60°	L110*W110*H110mm	L80*W80mm
12W	1800-2800K	600lm	95	21	15°/24°/38°/60°	L110*W110*H110mm	L80*W80mm



B0112-02/A2

Power	CCT	Lumen	CRI	IP	Beam Angle	Dimension	Cut-out
2*7W	2700/3000/4000K	1200lm	90	21	15°/24°/38°/60°	L180*W110*H85mm	L160*W80mm
2*7W	1800-2800K	760lm	95	21	15°/24°/38°/60°	L180*W110*H85mm	L160*W80mm
2*12W	2700/3000/4000K	2000lm	90	21	15°/24°/38°/60°	L180*W110*H110mm	L160*W80mm
2*12W	1800-2800K	1200lm	95	21	15°/24°/38°/60°	L180*W110*H110mm	L160*W80mm



B0112-02/A3

Power	CCT	Lumen	CRI	IP	Beam Angle	Dimension	Cut-out
3*7W	2700/3000/4000K	1800lm	90	21	15°/24°/38°/60°	L260*W110*H85mm	L240*W80mm
3*7W	1800-2800K	1140lm	95	21	15°/24°/38°/60°	L260*W110*H85mm	L240*W80mm
3*12W	2700/3000/4000K	3000lm	90	21	15°/24°/38°/60°	L260*W110*H110mm	L240*W80mm
3*12W	1800-2800K	1800lm	95	21	15°/24°/38°/60°	L260*W110*H110mm	L240*W80mm

2 IN 1 2 POWER + 3CCT SWITCH

- Power and CCT Switchable
- Multiple power box options
- Dimmable and NON-Dimmable
- 5 years and 10 years warranty options



Power :3~42W

PF:≥0.95

Flicker free and noise-free

Smooth triac Dimmable

Dimmable Range:10~100%

Dimmable power supply

CCT: 2700K/3000K/4000K

CCT: 2700K/4000K/6000K

CCT: 3000K/4000K/5500K

CRI.: 90

Luminous Efficiency: 130 LM/W MAX.

